## High Count

Premium High Count is designed to help solve problems on your toughest jobs. Our Premium High Count can be used for heavy grease break down, drainfield rejuvenation, municipal plants, sewer and later lines, sewage ponds, settling ponds, grease traps, pump stations, organic spills or where ever a problem area is detected. High Count can aid in the digestion of problem systems. It provides up to 3 times more bacteria and enzymes over most commercial bio-logical products. High Count was developed to help manage troublesome areas. Though the product is environmentally safe, precautions in handling need to be followed. Follow all safe handling procedures outlined in the MSDS. Premium High Count is available in 5 gallon pails and 50 lb. totes. Both products can be private labeled.

## **DIRECTIONS:**

Badly clogged or non-operating septic systems, drains, and grease traps should be cleaned before application. Product is designed to break down heavy grease and organic buildup. Product should be handled by professionals. Follow precautions when handling.

**Grease trap shock Treatment:** Outdoor traps, Pour 5 lbs. directly into grease trap. If necessary add water to hydrate product. Repeat as

necessary every two weeks. Small indoor traps use 1 lb. Repeat 2 weeks.

Lift Stations: Use 1 pound (4-cups) per lift station to shock system.

Continue with 1 - 2 cups every 3 days or 4 - 5 cups per week.

**Grease trap Normal Maintenance:** 1,000 gallon traps use ½ cup daily. Indoor traps use 1 tablespoon daily

**Septic systems, cesspools, open pits:** If the system is sluggish then shock treat system with 1 lbs. per 1000 gallons. If lateral lines are accessible then use 2 lbs. per lateral line. Continue with monthly pre-measured packet treatments. To oxidize a system use up to 5 lbs. per month for 100 feet of line. Add directly into the leach line or leach bed. Commercial chambered and pressure systems need specific sizes to properly dose. Follow the recommendations of your professional contractor.

**Sewage ponds, sewage systems, sewage holding tanks:** Application rates vary for these systems, use your cleaning professional's advice for application rates.

<u>First Aid & Precautions:</u> Contact may cause irritation to skin, eyes and lungs. Avoid contact with skin and eyes. Wash thoroughly after handling. In case of contact, flush eyes and skin with water for 15 minutes. If irritation continues seek medical attention. In case of ingestion, do not induce vomiting. Get immediate medical attention. Do not breath in dust. Wear appropriate dust mask when handling.

KEEP OUT OF REACH OF CHILDREN Not For Human Consumption

NON-POISONOUS ~ NON-TOXIC NON-CORROSIVE ~ NON-CAUSTIC









5 - gallon Pail



50 lb. - Tote